

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : A61L 9/03	A1	(11) International Publication Number: WO 98/46285 (43) International Publication Date: 22 October 1998 (22.10.98)
(21) International Application Number: PCT/US98/07898 (22) International Filing Date: 14 April 1998 (14.04.98) (30) Priority Data: 08/834,071 14 April 1997 (14.04.97) US (71) Applicant: S.C. JOHNSON & SON, INC. [US/US]; 1525 Howe Street, Racine, WI 53403 (US). (72) Inventors: MARTIN, John; 5305 Santa Anita Drive, Racine, WI 53402 (US). WEFLER, Mark, E.; 4937 High Meadows Terrace, Racine, WI 53406 (US). (74) Agents: FRANK, J., William, III et al.; S.C. Johnson & Son, Inc., Patent Section, 1525 Howe Street, Racine, WI 53403 (US).		(81) Designated States: AU, BR, CN, JP, KR, MX, NZ, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: DISPOSABLE PLUG-IN AIR FRESHENER



(57) Abstract

This invention provides a disposable air freshener dispenser device which is adapted for engagement and support by a wall electrical outlet. The dispenser device consists of a cartridge (12) which has a sealed content of liquid air freshener medium (30), and an absorbent matrix (14) which can be exposed for wicking of air freshener into the atmosphere. An electrical-resistance type heater module (11) is detachably secured and positioned proximate to the exposed absorbent matrix section for promotion of the wicking action.

## DISPOSABLE PLUG-IN AIR FRESHENER

TECHNICAL FIELD

This invention generally relates to dispensers of vaporizable media. More specifically, this invention relates to a device for dispensing a fragrance or  
5 deodorant in the form of a vapor for air freshening in an enclosed environment.

BACKGROUND OF THE INVENTION

The need for effectively combating airborne malodors in homes and enclosed public buildings, by odor masking or destruction, is well established. Various kinds of vapor-dispensing devices have been employed for this purpose.  
10 The most common of such devices is the aerosol container which propels minute droplets of an air freshener composition into the air. Another common type of dispensing device is a dish containing or supporting a body of gelatinous matter which when it dries and shrinks releases a vaporized air-treating composition into the atmosphere. Other products such as deodorant blocks are also used for  
15 dispensing air-treating vapors into the atmosphere by evaporation. Another group of vapor-dispensing devices utilizes a carrier material such as paperboard impregnated or coated with a vaporizable composition.

A number of recent developments include a liquid air-treating composition in an enclosure, all or part of which is formed of a polymeric film  
20 through which the air-treating composition can migrate to be released as a vapor at an outer surface. Use of this type of permeable polymeric membrane controls the dispensing of air-treating vapors and tends to eliminate great variations in the rate of dispensing over the life of the product. Wicking devices are well known for dispensing volatile liquids into the atmosphere, such as fragrance, deodorant,  
25 disinfectant or insecticide active agent.

A typical wicking device utilizes a combination of a wick and emanating region to dispense a volatile liquid from a liquid reservoir. Wicking devices are described in United States Patent Numbers 1,994,932; 2,597,195; 2,802,695;

2,804,291; 3,550,853; 4,286,754; 4,413,779; 4,454,987; 4,913,350; and 5,000,383; incorporated by reference.

Of special interest with respect to the present invention are wicking dispenser devices in which the wicking action is promoted by a heat source. This type of wicking device is described in United States Patent Numbers 3,288,556; 3,431,393; 3,482,929; 3,633,881; 4,020,321; 4,968,487; 5,038,394; 5,290,546; and 5,364,027; incorporated by reference.

Some air freshener dispensers are expensive to manufacture. Other air freshener dispensers are inexpensive to produce, but tend to have inferior construction and functionality.

There remains a need for a well-constructed air freshener dispenser device which can be mass-produced economically and which can deliver a vapor medium at a controlled uniform rate over an extended period of time.

Accordingly, it is an object of this invention to provide an improved air freshener dispenser device for delivering an odorant and/or deodorant vapor in an enclosed environment.

It is another object of this invention to provide an air freshener dispenser device with a primary structure which is a plastic assembly that can be produced economically by a thermoforming means.

It is another object of this invention to provide a disposable air freshener dispenser device which has an interactive combination of electrical-resistance heater module and air freshener cartridge unit.

It is a further object of this invention to provide an air freshener cartridge for utility in a heat-activated air freshener dispenser device, wherein the cartridge has an internal air freshener reservoir in contact with a wicking means.

Other objects and advantages of the present invention shall become apparent from the accompanying description and drawings.

### SUMMARY DESCRIPTION OF INVENTION

One or more objects of the present invention are accomplished by the provision of a disposable air freshener dispenser device which is adapted for engagement and support by a wall electrical outlet, and which is an assembly of

5 structural units comprising:

(1) a cartridge which comprises

(a) a thermoplastic tray having side walls with an upper edge flange which forms a peripheral margin around the open space of the tray, wherein the flange has an elongated extension from one wall, and the surface of the elongated flange extension has a shallow flat recess extending from the wall edge,

10

(b) a thin emanating absorbent matrix with an upper section which fits within the flange flat recess, and with a lower section which extends across the open space of the tray to the opposite wall edge,

15

(c) a volatile liquid air freshener medium which is contained within the tray interior,

(d) a first vapor-impermeable membrane which covers the open space of the tray and the lower section of the absorbent matrix, and which is bonded to the tray peripheral margin and forms a sealed air freshener reservoir enclosure within the tray interior, and

20

(e) a peelable second vapor-impermeable membrane which covers the upper section of the absorbent matrix; and

25

(2) an electrical-resistance type heating means which is detachably secured and positioned proximate to the back surface of the tray elongated flange extension and the upper section of the absorbent

matrix for promotion of air freshener wicking into the atmosphere,  
wherein the heating means comprises

- (a) a molded plastic electrical plug housing with a flat front surface and two inlet openings within the plug housing,
- 5 (b) a detachable thin panel section which is juxtapositioned on the flat front surface of the plug housing, wherein the panel section comprises an electrical-resistance heater module, and has two apertures corresponding in position to the inlet openings within the plug housing, and
- 10 (c) a pair of metal prongs which are positioned within the apertures of the panel section and the inlet openings of the plug housing, and which extend rearwardly from the plug housing for engagement with a wall electrical outlet, and said prongs are adapted to conduct electric current to the
- 15 electrical-resistance heater module.

In another embodiment this invention provides a disposable air freshener dispenser device which is adapted for engagement and support by a wall electrical outlet, and which prior to assembly is an aggregate of conformational structural units comprising:

- 20 (1) cartridge components which comprise
  - (a) a thermoplastic tray having side walls with an upper edge flange which forms a peripheral margin around the open space of the tray, wherein the flange has an elongated extension from one wall, and the surface of the elongated
  - 25 flange extension has a shallow flat recess extending from the wall edge,
  - (b) a thin emanating absorbent matrix which fits within the flange flat recess, and has a lower section extendable

-5-

across the open space of the tray to the opposite wall edge,  
and

- (c) a vapor-impermeable membrane which is bondable to the tray peripheral margin to form a sealed air freshener reservoir enclosure within the tray interior; and
- (2) plug-in electrical-resistance type heating components which comprise
  - (a) a molded plastic electrical plug housing with a flat front surface and two inlet openings within the plug housing,
  - (b) a thin panel section which comprises an electrical-resistance heater module, and has two apertures with position correspondence to the inlet openings within the plug housing, and
  - (c) a pair of metal prongs for positioning within the apertures of the panel section and the inlet openings of the plug housing, wherein said prongs are adapted to conduct electric current to the electrical-resistance heater module in the assembled dispenser device having a reservoir content of liquid air freshener medium.

#### DESCRIPTION OF DRAWINGS

FIG. 1 is a composite perspective view of an invention air freshener dispenser device.

FIG. 2 is a perspective front view of an invention device plug-in electrical-resistance heater module.

FIG. 3 is an elevational front view of an invention disposable air freshener dispenser device after removal of a peelable vapor-impermeable membrane.

FIG. 4 is an elevational front view of a FIG. 3 invention dispenser device with a vented cover in a closed position.

FIG. 5 is an elevational side view of a FIG. 4 invention dispenser device with rearwardly extended metal prongs, and a reservoir content of liquid air freshener medium.

## 5 BEST MODE FOR CARRYING OUT THE INVENTION

FIG. 1 illustrates an exploded view of present invention air freshener dispenser device 10 without a liquid air freshener medium content.

In assembled form, air freshener dispenser device 10 is plugged into a wall electrical outlet by means of twin prongs 23 of heater module 11. Electric  
10 current is conducted by twin prongs 23 to printed electrical-resistance heating pattern 25 for promotion of liquid air freshener wicking out of the interior reservoir of cartridge 12 by absorbent matrix 14 after removal of peelable vapor-impermeable membrane 16.

FIG. 2 is a perspective front view of plug-in electrical-resistance heater  
15 module 11 in assembled form. Vented cover 21 is attached to electrical plug housing 20 by flexible hinge 28. As illustrated, electrical plug housing 20 and vented cover 21 together constitute a single unitary plastic structure formed by molding means from a thermoset polymer such as phenol-formaldehyde resin, epoxy resin, polyphenylene sulfide, polyphenylene oxide, polycarbonate,  
20 polyimide, polybenzimidazole, and the like, or a thermoplastic polymer such as polyethylene, polypropylene, polyamide, and the like.

Printed electrical-resistance heating pattern 25 on panel section 22 in FIG. 2 heater module 11 can be in the form of an electric-conductive ink or electric-conductive polymer with electrical-resistance properties for heat  
25 generation. Printed or thin film electrical-resistance heating elements are described in publications such as United States Patent Numbers 3,067,310; 3,266,661; 4,849,255; 4,857,384; 4,912,306; 4,935,156; 5,106,540; 5,382,384; and 5,415,934; incorporated by reference. Panel section 22 can be a thermoset

-7-

polymer such as Novalak resin, or a thermoplastic polymer such as polyvinyl chloride or polyvinyl acetate.

Cover 21 in FIG. 2 heater module 11 has at least one vent aperture 27 for release of air freshener vapor when invention air freshener dispenser device 10 is operational. Vent aperture 27 can have an adjustable open-close feature.

FIG. 3 is an elevational front view of invention air freshener dispenser device 10 after removal of peelable vapor-impermeable membrane 16, which can be a thin flexible material such as aluminum foil or nylon film. Tab section 17 facilitates the removal of membrane 16, for exposure of the upper emanating surface of absorbent matrix 14.

As illustrated in FIG. 3, after removal of vapor-impermeable membrane 16, liquid air freshener medium 30 is wicked by capillary action up absorbent matrix 14 out of the interior reservoir of cartridge 12, and is vaporized into the atmosphere. Vapor-impermeable membrane 18 is bonded to flange 13 to form a sealed air freshener reservoir enclosure in cartridge 12. Membrane 18 can be formed of different or the same material as membrane 16. Preferably, membrane 18 is translucent or transparent for viewing the level of air freshener 30 in cartridge 12. In another embodiment, membrane 16 and membrane 18 are taken together in the form of a single thin film, which has a peelable area for exposure of the upper section of emanating absorbent matrix 14 to allow air freshener wicking into the atmosphere.

FIG. 4 is an elevational front view of FIG. 3 invention dispenser device 10 with vented cover 21 in a closed position. Typically cartridge 12 is a translucent or transparent structure which is injection or thermoform molded from a polymer such as polyethylene, polypropylene, polystyrene, polyvinyl chloride, polyvinyl acetate, polyamide, polymethacrylate, and the like.

FIG. 5 is an elevational side view of FIG. 4 invention dispenser device 10 which illustrates the rearward positioning of brass prongs 23 for accessing a wall electrical outlet.



Cartridge 12 of invention dispenser device 10 as illustrated in FIGS. 3-5 typically has rectangular flange periphery dimensions between about 1-3 inches in width and 2-6 inches in length. The tray reservoir depth optionally can vary between about 0.2-0.6 inches.

5        Absorbent matrix 14 in FIGS. 3-5 can be an organic or inorganic liquid-permeable structure, such as a porous thermoplastic, thermoset, cellulosic or ceramic composition. The dimensions of absorbent matrix 14 are adapted to frictionally secure the structure within the conformational recesses provided in flange 13 of cartridge 12. Absorbent matrix 14 also can be in the form of a  
10        fibrous aggregate or a grooved nonporous strip. A variety of wick compositions and structures suitable for air freshener dispenser devices are described in United States Patent Numbers 3,431,393; 3,482,929; 3,633,881; 4,020,321, 4,968,487; 5,038,394; and 5,290,546; incorporated by reference.

      Air freshener medium 30 in FIGS. 3-5 can be any air treating material  
15        which can be wicked up absorbent matrix 14 by capillary action, and dispersed into the atmosphere in vapor form. Typically air freshener medium 30 is a fragrance or a deodorant formulation in liquid form.

      Air freshener medium 30 preferably is a liquid fragrance comprising one or more volatile organic compounds which are available from perfumery  
20        suppliers such as Firmenich Inc., Takasago Inc., Noville Inc., Quest Co., and Givaudan-Roure Corp.

      Most conventional fragrance materials are volatile essential oils. The fragrance can be a synthetically formed material, or a naturally derived oil such as oil of Bergamot, Bitter Orange, Lemon, Mandarin, Caraway, Cedar Leaf, Clove  
25        Leaf, Cedar Wood, Geranium, Lavender, Orange, Origanum, Petitgrain, White Cedar, Patchouli, Lavandin, Neroli, Rose absolute, and the like.

      A wide variety of chemicals are known for perfumery, such as aldehydes, ketones, esters, alcohols, terpenes, and the like. A fragrance can be relatively

simple in composition, or can be a complex mixture of natural and synthetic chemical components.

A typical scented oil can comprise woody/earthy bases containing exotic constituents such as sandalwood oil, civet, patchouli oil, and the like. A scented  
5 oil can have a light floral fragrance, such as rose extract or violet extract. Scented oil also can be formulated to provide desirable fruity odors, such as lime, lemon or orange.

Synthetic types of fragrance compositions either alone or in combination with natural oils are described in United States Patents 4,314,915; 4,411,829; and  
10 4,434,306; incorporated herein by reference. Other artificial liquid fragrances include geraniol, geranyl acetate, eugenol, isoeugenol, linalool, linalyl acetate, phenethyl alcohol, methyl ethyl ketone, methylionone, isobornyl acetate, and the like.

Air freshener medium 30 also can be a liquid formulation containing a  
15 volatile pesticide such as p-dichlorobenzene, or a therapeutic agent such as menthol.

Air freshener dispenser device 10 preferably is constructed of transparent or translucent materials, such that air freshener medium 30 is visible during usage for an indication of the liquid level in the interior reservoir of  
20 cartridge 12.

A present invention air freshener dispenser device can be produced in high volume from relatively inexpensive plastic materials. After usage, the device qualifies for disposal as a non-hazardous solid waste.

#### INDUSTRIAL APPLICABILITY:

25 The present invention is useful as a low cost vapor dispensing device, for example, as a room air freshener.

WHAT I CLAIM IS:

1. A disposable air freshener dispenser device which is adapted for engagement and support by a wall electrical outlet, and which is an assembly of structural units comprising:

- 5 (1) a cartridge which comprises
- (a) a thermoplastic tray having side walls with an upper edge flange which forms a peripheral margin around the open space of the tray, wherein the flange has an elongated extension from one wall, and the surface of the elongated  
10 flange extension has a shallow flat recess extending from the wall edge,
  - (b) a thin emanating absorbent matrix with an upper section which fits within the flange flat recess, and with a lower section which extends across the open space of the tray to  
15 the opposite wall edge,
  - (c) a volatile liquid air freshener medium which is contained within the tray interior,
  - (d) a first vapor-impermeable membrane which covers the open space of the tray and the lower section of the  
20 absorbent matrix, and which is bonded to the tray peripheral margin and forms a sealed air freshener reservoir enclosure within the tray interior, and (e) a peelable second vapor-impermeable membrane which covers the upper section of the absorbent matrix; and
- 25 (2) an electrical-resistance type heating means which is detachably secured and positioned proximate to the back surface of the tray elongated flange extension and the upper section of the absorbent matrix for promotion of air freshener wicking into the atmosphere, wherein the heating means comprises

-11-

- 5 (a) a molded plastic electrical plug housing with a flat front surface and two inlet openings within the plug housing,
- (b) a detachable thin panel section which is juxtapositioned on the flat front surface of the plug housing, wherein the panel section comprises an electrical-resistance heater module, and has two apertures corresponding in position to the inlet openings within the plug housing, and
- 10 (c) a pair of metal prongs which are positioned within the apertures of the panel section and the inlet openings of the plug housing, and which extend rearwardly from the plug housing for engagement with a wall electrical outlet, and said prongs are adapted to conduct electric current to the electrical-resistance heater module.
- 15 2. A dispenser device in accordance with claim 1 wherein the cartridge thermoplastic tray is a molded polyvinyl structure with transparency, and the air freshener medium in the tray interior reservoir is visible.
- 20 3. A dispenser device in accordance with claim 1 wherein the absorbent matrix is a porous wick structure selected from the group consisting of thermoplastic, thermoset, cellulosic and ceramic compositions.
4. A dispenser device in accordance with claim 1 wherein the liquid air freshener is a fragrance formulation.
- 25 5. A dispenser device in accordance with claim 1 wherein the first and second vapor-impermeable membranes are selected from aluminum foil and nylon film.
6. A dispenser device in accordance with claim 1 wherein the first and second vapor-impermeable membranes taken together constitute a single thin film which
- 30

-12-

has a peelable section for exposure of the emanating absorbent matrix for air freshener wicking.


7. A dispenser device in accordance with claim 1 wherein the electrical plug housing is a molded thermoset or thermoplastic polymer structure.
8. A dispenser device in accordance with claim 1 wherein the electrical-resistance heater module comprises a thin panel section with a surface microfilm coating of electric-conductive polymer.
9. A dispenser device in accordance with claim 1 which additionally has a vented cover that overlays the tray flange extension and the absorbent matrix upper section, and is detachably secured to the electrical plug housing.
10. A dispenser device in accordance with claim 9 wherein the electrical plug housing and the vented cover are integrally molded as a single plastic unit, and the vented cover is attached by a flexible hinge means to one side of the said electrical plug housing.
11. A disposable air freshener dispenser device which is adapted for engagement and support by a wall electrical outlet, and which prior to assembly is an aggregate of conformational structural units comprising:
- (1) cartridge components which comprise
    - (a) a thermoplastic tray having side walls with an upper edge flange which forms a peripheral margin around the open space of the tray, wherein the flange has an elongated extension from one wall, and the surface of the elongated flange extension has a shallow flat recess extending from the wall edge,





-13-

- (b) a thin emanating absorbent matrix which fits within the flange flat recess, and has a lower section extendable across the open space of the tray to the opposite wall edge, and
- 5 (c) a vapor-impermeable membrane which is bondable to the tray peripheral margin to form a sealed air freshener reservoir enclosure within the tray interior; and
- (2) plug-in electrical-resistance type heating components which comprise
  - 10 (a) a molded plastic electrical plug housing with a flat front surface and two inlet openings within the plug housing,
  - (b) a thin panel section which comprises an electrical-resistance heater module, and has two apertures with position correspondence to the inlet openings within the plug housing, and
  - 15 (c) a pair of metal prongs for positioning within the apertures of the panel section and the inlet openings of the plug housing, wherein said prongs are adapted to conduct electric current to the electrical-resistance heater module in
  - 20 the assembled dispenser device having a reservoir content of liquid air freshener medium.

INDUSTRIAL APPLICABILITY:

1 / 2







# INTERNATIONAL SEARCH REPORT

In. Application No  
PCT/98 98/07898

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 A61L9/03

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 A61L A01M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE 44 46 413 A (GLOBOL GMBH) 27 June 1996 see claims; figures 1-6 ---	1-11
Y	DE 41 31 613 A (GLOBOL GMBH) 25 March 1993 see claims; figures ---	1-11
A	WO 94 15650 A (CULMSTOCK LTD ; PAUL DUNCAN J (GB); MARSH JOHN REES (GB); SMITH NIG) 21 July 1994 see claims; figures ---	1-11
A	DE 36 09 511 A (OREAL) 16 October 1986 see figures ---	1-11
A	GB 2 275 608 A (JOHNSON & SON INC S C) 7 September 1994 see figures 1-9 ---	1-11
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

28 September 1998

Date of mailing of the international search report

05/10/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

ESPINOSA, M

# INTERNATIONAL SEARCH REPORT

In. Application No  
PCT/83 98/07898

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 2 432 837 A (GLOBOL WERK) 7 March 1980 ---	
A	EP 0 689 766 A (FALP SRL) 3 January 1996 ---	
A	WO 96 33605 A (RECKITT & COLMAN INC) 31 October 1996 -----	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

In Application No

PCT/US 98/07898

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 4446413 A	27-06-1996	AU 695612 B AU 4020095 A BR 9505736 A CN 1133257 A EP 0722742 A JP 8244842 A ZA 9510121 A	20-08-1998 04-07-1996 23-12-1997 16-10-1996 24-07-1996 24-09-1996 06-06-1996
DE 4131613 A	25-03-1993	NONE	
WO 9415650 A	21-07-1994	AU 5837394 A	15-08-1994
DE 3609511 A	16-10-1986	FR 2581878 A AT 391270 B AT 73786 A BE 904443 A	21-11-1986 10-09-1990 15-03-1990 19-09-1986
GB 2275608 A	07-09-1994	NONE	
FR 2432837 A	07-03-1980	DE 7823826 U DK 333379 A NL 7906097 A SE 7906454 A	08-02-1979 11-02-1980 12-02-1980 11-02-1980
EP 0689766 A	03-01-1996	NONE	
WO 9633605 A	31-10-1996	US 5647052 A AU 5570896 A EP 0824305 A	08-07-1997 18-11-1996 25-02-1998